

NOTES:

1. CLEANOUT TO BE PLACED AT OR NEAR THE PROPERTY LINE.
2. CLEANOUT TO BE BROUGHT TO GRADE WITH AN ACCESSIBLE CAP.
3. METAL COVERS SHALL BE INSTALLED ON ALL CLEANOUTS INSTALLED WITHIN HARD SURFACES. (EG.DRIVEWAYS, SIDEWALKS AND LEADWALKS)
4. HOME BUILDER SHALL CONNECT PDC TO TEE. NO CONNECTIONS SHALL BE MADE TO THE RISER PIPE.
5. PIPE MATERIAL AND FITTINGS SHALL BE SMOOTH WALL, GASKETED, PVC SDR 28 CONFORMING TO CSA B182.2. PRIVATE DRAIN CONNECTION AND CLEANOUT PIPES SHALL BE 150mm DIAMETER AND COLOUR CODED TO AVOID CROSS CONNECTIONS. ALL SANITARY PRIVATE DRAIN CONNECTIONS SHALL BE GREEN PVC AND ALL STORM PRIVATE DRAIN CONNECTIONS SHALL BE WHITE PVC.
6. TO BE READ IN CONJUNCTION WITH CITY STANDARD SPECIFICATION S-1 AND S-35 AND AS-313.

NOT TO SCALE

CITY OF WINDSOR

ENGINEERING DEPARTMENT

CLEANOUT AT PROPERTY LINE

DR'N BY: JL, AZ	DATE: FEB, 2000
REV. DATE: JUN, 2024	CH'KD BY(ENG): PM, JH
CH'KD BY(GEO/OPS): PJU, AL	PASSED BY: FM

Mark Winterton
Digitally signed by Mark Winterton
Date: 2024.07.08 12:13:09 -04'00'
CITY ENGINEER

AS-325